

AC118 Series

High G Measurement Accelerometer, Side Exit 2 Pin Connector, 50 mV/g, ±10%




Product Features

50 mV/g General Purpose Side Exit Sensor
Excellent for Higher g Applications

- ▶ ±100 g, Dynamic Range
- ▶ 50 mV/g, ±10% Sensitivity
- ▶ 1,0-10000 Hz (60-600,000 CPM)

AC118-1A
2 Pin Connector


Connector	Polarity
Pin	
A	(+) Signal/Power
B	(-) Common



Stock Product

AC118-2C
CB103 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

AC118-3C
CB206 Armored Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

AC118-6C
CB611 Heavy Duty Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC118	M/AC118	Environmental		
Sensitivity (±10%)	50 mV/g		Operating Temperature Range	-58 to 250°F	-50 to 121 °C
Frequency Response (±3dB)	60-600,000 CPM	1,0-10000 Hz	Maximum Shock Protection	5,000 g, peak	
Frequency Response (±10%)	240-360,000 CPM	4,0-6000 Hz	Electromagnetic Sensitivity	CE	
Dynamic Range	± 100 g, peak *Vsource ≥ 22V, 12Vbias		Sealing	Welded, Hermetic	
Electrical			Submersible Depth	200 ft.	60 m
Settling Time	<2 Seconds		SIL Rating	SIL 2	
Voltage Source (IEPE)	18-30 VDC		Physical		
Constant Current Excitation	2-10 mA		Sensing Element	PZT Ceramic	
Spectral Noise @ 10 Hz	8 µg/√Hz		Sensing Structure	Shear Mode	
Spectral Noise @ 100 Hz	2.5 µg/√Hz		Weight	5.1 oz	145 grams
Spectral Noise @ 1000 Hz	1.7 µg/√Hz		Case Material	316L Stainless Steel	
Output Impedance	<100 ohm		Connector (Non-Integral)	2 Pin MIL-C-5015	
Bias Output Voltage	10-14 VDC		Resonant Frequency	1,260,000 CPM	21000 Hz
Case Isolation	>10 ⁸ ohm		Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm