

AC961 Series

Low Capacitance, Intrinsically Safe IEC Certified (IECEX / ANZEx / PESO) Accelerometer, Top Exit 2 Pin Connector, 10 mV/g, ±10%



CE
IECEX
ANZEx
PESO
UK
CA




Regulatory Information

Ex ia IIC T3/T4
AEx ia IIC T3/T4
CLI Groups A, B, C, D
CLII Groups F, G
CLIII

Ui = 28 Vdc li = 100 mA
CSA 221421
IECEX CSA 07.0001
Ex ia IIC T3
Ex ia IIC T4
Operating Temperature Code: T4 ANZEx 18.4160
Ambient Temperature Range =
-40 to 80°C
Operating Temperature Code: T3
Ambient Temperature Range =
-40 to 125°C

AC961-1A
2 Pin Connector


Connector	Polarity
Pin	
A	(+) Signal/Power
B	(-) Common



Stock Product

AC961-2C
CB193 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

AC961-3C
CB296 Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC961	M/ or M8/AC961	Environmental		
Sensitivity (±10%)	10 mV/g		Operating Temperature Range	-40 to 250 °F	-40 to 121 °C
Frequency Response (±3dB)	72-900,000 CPM	1,2-15000 Hz	Maximum Shock Protection	5,000 g, peak	
Frequency Response (±10%)	150-360,000 CPM		Electromagnetic Sensitivity	CE	
Dynamic Range	± 500 g, peak		Sealing	Welded, Hermetic	
Electrical			Submersible Depth	200 ft.	61 m
Settling Time	<3 Seconds		Physical		
Voltage Source (IEPE)	18-28 VDC		Sensing Element	PZT Ceramic	
Constant Current Excitation	2-4 mA		Sensing Structure	Shear Mode	
Spectral Noise @ 10 Hz	500 µg/√Hz		Weight	3.2 oz	90 grams
Spectral Noise @ 100 Hz	65 µg/√Hz		Case Material	316L Stainless Steel	
Spectral Noise @ 1000 Hz	11 µg/√Hz		Mounting Thread	1/4-28 Blind Tapped Hole	
Output Impedance	<100 ohm		Connector (Non-Integral)	2 Pin MIL-C-5015	
Bias Output Voltage	10-14 VDC		Resonant Frequency	1,380,000	23000 Hz
Case Isolation	>10 ⁸ ohm				