


LP812-XXX-5XC Series

Low Capacitance, Intrinsically Safe Loop Power Sensor, 4-20 mA
Output Proportional to Vibration in Velocity, Top Exit with Flying
Leads




Product Features

- Continuous Monitoring in Hazardous Locations
- Velocity 4-20 mA Output for Applications in Hazardous Locations
- ▶ CSA and ATEX Approvals
 - ▶ Intrinsic safe applications with use of barrier
 - ▶ With 1 inch NPT conduit fitting, Integral 1/4 - 18 NPT Mounting Stud

LP812-XXX-51C
1/4 inch NPT Mount


Conductor	Polarity
Red	(+) Loop Power mA Output
Black	(-) Common



Built To Order

LP812-XXX-52C
1/2 inch NPT Mount

Conductor	Polarity
Red	(+) Loop Power mA Output
Black	(-) Common



Built To Order

Specifications	Standard	Metric
Tolerance: 4 mA	(± 10%)	
Tolerance: 20 mA	(± 10%)	
Electrical		
Settling Time	<60 Seconds	
Voltage Source (IEPE)	12-28 VDC	
Case Isolation	>10 ⁸ ohm	
Environmental		
Operating Temperature Range	-4 to 176°F	-20 to 80°C
Electromagnetic Sensitivity	CE	
Sealing	IP68	

Specifications	Standard	Metric
Physical		
Sensing Element	PZT Ceramic	
Sensing Structure	Shear Mode	
Weight	12 oz	340 grams
Case Material	316L Stainless Steel	
Mounting Thread	1/4 NPT (LP812-51C) 1/2 NPT (LP812-52C)	
Connector (Non-Integral)	Flying Leads	
Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
Calibration Certificate	Current Output @ 100 Hz	

Ordering Information

LP - -