

TXGA333 Series

Low Frequency Triaxial Accelerometer, Side Exit 4 Pin Connector,
1,000 mV/g, ±15%



Product Features


Collect 3 Channels of Data Simultaneously for
Faster Data Collection

Follows Cartesian Coordinate Phase
Configuration (Right Hand Rule)

- ▶ Designed for Low Speed Applications such as
Low Speed Rotors, Main Bearings, and Gear
Box Inputs.
- ▶ Mini-MIL Connector Exit Option Compatible
CTC J Series Mini-MIL Connectors
- ▶ M12 Connector Exit Option Compatible with
CTC M4 Series Connectors

TXGA233
4 Pin M12 Connector


Connector Pin	Polarity
1 (Axis Y)	(+) Signal/Power
2 (Axis X)	(+) Signal/Power
3 (Axis Z)	(+) Signal/Power
4	(-) Common



Stock Product

TXGA333
4 Pin Mini-MIL Connector


Connector Pin	Polarity
A (Axis Y)	(+) Signal/Power
B (Axis X)	(+) Signal/Power
C (Axis Z)	(+) Signal/Power
D	(-) Common/Grd



Stock Product

TXGA433
CB105 Integral Cable


Conductor	Polarity
Red (Axis Y)	(+) Signal/Power
Green (Axis X)	(+) Signal/Power
White (Axis Z)	(+) Signal/Power
Black	(-) Common/Grd



Built To Order

TXGA533
CB218 Armored Integral Cable

Conductor	Polarity
Red (Axis Y)	(+) Signal/Power
Green (Axis X)	(+) Signal/Power
White (Axis Z)	(+) Signal/Power
Black	(-) Common/Grd



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	TXGA333	M/TXGA333	Environmental		
Sensitivity (±15%)	1,000 mV/g		Operating Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (±3dB)	6-420,000 CPM	0,1-7,000 Hz	Maximum Shock Protection	5000 g, peak	
Frequency Response (±10%)	18-180,000 CPM	0,3-3000 Hz	Electromagnetic Sensitivity	CE	
Dynamic Range	± 7 g, peak *Vsource ≥ 22V, 12Vbias		Sealing	Welded, Hermetic	
Electrical			Submersible Depth	200 ft.	60 m
Settling Time	< 2 seconds		SIL Rating	SIL 2	
Voltage Source (IEPE)	18-30 VDC		Physical		
Constant Current Excitation	2-10 mA		Sensing Element	PZT Ceramic	
Spectral Noise @ 10 Hz	1.3 µg/√Hz		Sensing Structure	Shear Mode	
	0.2 µg/√Hz		Weight	13.4 oz	380 grams
			Case Material	316L Stainless Steel	
				4 Pin	