


PIN	FUNCTION	
	SINGLE SUPPLY OR 4-20mA OUTPUT	DUAL SUPPLY
A	+VDC	+VDC
B	PWR & SIG COM	PWR & SIG COM
C	N/C	-VDC
D	SIG OUT	SIG OUT
E	N/C	N/C
F	N/C	N/C

NOTES:

- DATUM **- A -** AND **- B -** ARE DEFINED AS REFERENCE SURFACES.
- CONNECTOR: PT02H-10-6P  
MATES WITH: PT06A-10-6S (SR)
- UNITS: [mm]  
INCH

DIMENSIONS ARE IN INCHES AND APPLY TO PART BEFORE FINISHING		 <b>Jewell Instruments</b> MANCHESTER, NH TRIPLETT MODUTEC A&M EMICO	TITLE <b>LSOX-C OUTLINE DRAWING</b>	
TOLERANCE UNLESS SPECIFIED TWO PLACE DECIMALS (.00) ± .01 THREE PLACE DECIMALS (.000) ± .005 ANGLES ± 1° RAW MATL - COMMERCIAL STANDARD			DRAWING NO. <b>OD02550336-000</b>	REV <b>C</b>
PROPRIETARY NOTICE THIS DOCUMENT IS THE PROPERTY OF JEWELL INSTRUMENTS, LLC. NEITHER THIS DOCUMENT NOR THE DATA CONTAINED HEREIN SHALL BE DISCLOSED, REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN AUTHORIZATION OF JEWELL INSTRUMENTS, LLC. NO RIGHT IS GRANTED TO DISCLOSE OR SO USE ANY INFORMATION CONTAINED HEREIN. ALL RIGHTS RESERVED.		SCALE <b>1:1</b>	CAGE CODE 33005	SHEET 1 OF 1